

IES 4812 LED Controller



PRELIMINARY SHORTFORM DATA

Stationary LED Controller module for high speed video, mountable in 19" cases or racks. Can power LED Heads up to 1 kW. Ethernet and RS485 interfaces.

- ☺ **Synced or NonSynced lighting modes**
- ☺ **Isolated I/O-Interface, Ready and Start**
- ☺ **CMD-Interface (PC-Software)**
- ☺ **Module width 28 TE**
- ☺ **Desk top and rack mount cases available**



IES Ingenieurbüro für Elektronikentwicklung und Spezialgerätebau

Postanschrift
In den Waashainen 2
D-38108 Braunschweig

FON +49 531 701273-0
FAX +49 531 701273-19

Bankverbindung Postbank Hannover
BLZ 250 100 30, Konto 905 693 302
UStIDNr. DE 177335140

Specifications

Metrics	
Dimensions	142 x 128 x 172 mm ³
Weight	2.1 kg

Environment	
Temperature range	0°C ... +40°C
Acceleration	stationary use only

Electrical Interface	
Rear side connector	DIN 41612
Power	110-230 VAC, 1 kW
Control/Status	Lemosia FGG.1B.308
Sync-Input	BNC
LED-Head Connector	Lemosia FGG.2B.310
Ready-Signal	Optoisolated Output
Start-Signal	Optoisolated Input

Ordering information: IES 4812

Also available:

- IES 4420 Mini LED Head 12000 lm
- IES 4421 Mini LED Head 24000 lm
- IES 4422 Mini LED Head 12000 lm
- IES 4425 LED Head 48000 lm
- IES 4432 LED Sync Lamp 96000 lm
- IES 4415 OnBoard LED-Controller
- IES 4416 OnBoard LED-Controller

Information is provided without warranty and is subject to change without notice. We reserve the right to make changes whenever necessary to improve to the product.

Revision 2019-06