

IES 4412 LED CONTROLLER

Stationary LED Controller for high speed video



- ▶ For LED-Heads up to 96000 lm
- ▶ Synced or NonSynced lightning modes
- ▶ Isolated I/O - Interface, Ready and Start
- ▶ RS-485 CMD-Interface (PC-Software)
- ▶ Dimensions 216 x 108 x 45 mm³ / 8.5" x 4.2" x 1.8"

SPECIFICATIONS

Metrics	
Dimensions	330 x 165 x 85 mm ³ / 8.5" x 4.2" x 1.8"
Weight	4.5 kg / 9.9 lb
Environment	
Temperature range	0...50 °C
Acceleration	
Electrical Interface	
Mains	100 - 240 VAC, 1W
Control/Status	Lemoso FGG, 1B.308
Sync - Input	BNC
LED - Head Connector	Lemoso FGG.3B.318
Ready signal	Opto - isolated Output
Start - signal	Opto - isolated Input

Ordering information: IES 4412

Also available:

IES 4420 Mini LED Head 12000 lm
 IES 4421 Mini LED Head 24000 lm
 IES 4422 Mini LED Head 12000 lm
 IES 4424 LED Sync Lamp 96000 lm
 IES 4416 OnBoard LED-Controller

Information is provided without warranty and is subject to change without notice. We reserve the right to make changes whenever necessary to improve the product. Revision 2012-02