

IES 4425-4 LED HEAD

PRELIMINARY SHORTFORM DATA

Modular LED Head for high speed video.



- ▶ 48000 lm
- ▶ Selectable illumination angles
- ▶ Modular design for building Arrays
- ▶ Dimensions 108 x 108 x 45 mm³ / 4.2" x 4.2" x 1.8"
- ▶ Lilon LED Supply/Controller available
- ▶ Ruggedized for onboard and offboard use

SPECIFICATIONS

Metrics	
Dimensions	108 x 108 x 45 mm ³ / 4.2" x 4.2" x 1.8"
Weight	1 kg / 2.2 lb

Environment	
Temperature range	0 ... 50°C
Acceleration	100 g.

Electrical Interface	
Connector	Lemo 1B.306

Illumination Parameters	
Illumination angle	45° (standard, others on request)

Ordering information: IES 4425-4

Also available:

IES 4420 Mini LED Head 12000 lm
IES 4421 Mini LED Head 24000 lm
IES 4422 Mini LED Head 12000 lm
IES 4424 LED Sync Lamp 96000 lm
IES 4412 Stationary LED Controller
IES 4414 Onboard LED Controller
IES 4416 OnBoard LED-Controller

Information is provided without warranty and is subject to change without notice. We reserve the right to make changes whenever necessary to improve the product. Revision 2012-08